



**[EN]** Reinforced safety cable grip with two eyes without thimbles, for high pressure pipes **[D]** Sicherheits-Kabelziehstrumpf für Hochdruckleitungen mit zwei Schleifen, verstärkte Ausführung **[E]** Malla de seguridad reforzado, para mangueras de alta presión, con doble lazo sin dedales **[F]** Chaussette de sécurité renforcée pour les flexibles haute pression, à boucle double sans cosse coeur **[I]** Calza di sicurezza rinforzata per tubi ad alta pressione, con 2 asole senza redancia

| art.         | ø mm   | L mm | L <sub>1</sub> mm |                   |    |        | n. |    | [mm]     | kg   |
|--------------|--------|------|-------------------|-------------------|----|--------|----|----|----------|------|
| XAP25402OSA  | 25-40  | 1050 | 800               | <b>7.000 daN</b>  | 6  | 2,0 mm |    | 19 | 8 x 10   | 1,25 |
| XAP35502OSA  | 35-50  | 1200 | 900               | <b>10.000 daN</b> | 6  | 2,0 mm |    | 19 | 8 x 10   | 1,55 |
| XAP50802OSA  | 50-80  | 1300 | 1000              | <b>12.000 daN</b> | 8  | 2,0 mm |    | 19 | 10 x 120 | 2,10 |
| XAP801052OSA | 80-105 | 1500 | 1200              | <b>15.000 daN</b> | 10 | 2,0 mm |    | 19 | 10 x 120 | 2,85 |

