


EYE COVERED

**[EN]** Cable grip fit for pulling or suspension, with one eye covered by plastic **[D]** Kabelzieh- oder Montagestrumpf mit einer kunststoffbeschichteten Schlaufe **[E]** Malla tiracables o portadores, con un lazo recubierto de materia plástica **[F]** Chaussette tire-câbles ou porteurs, a boucle simple avec revêtement en matière plastique **[I]** Calza tiracavi o di sospensione, con un'asola ricoperta in materiale plastico

| art.     | ø mm  | L mm | L <sub>1</sub> mm |  |  |  | n.                                                                                 |  |  | kg   |
|----------|-------|------|-------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------|
| XSTT1015 | 10-15 | 750  | 500               | 2.000 daN                                                                         | 4                                                                                 | 1,25 mm                                                                           |  | 19                                                                                  | 5 x 200                                                                             | 0,25 |
| XSTT1520 | 15-20 | 800  | 550               | 2.700 daN                                                                         | 5                                                                                 | 1,25 mm                                                                           |                                                                                    | 19                                                                                  | 5 x 200                                                                             | 0,32 |
| XSTT2030 | 20-30 | 850  | 600               | 3.500 daN                                                                         | 5                                                                                 | 1,50 mm                                                                           |                                                                                    | 19                                                                                  | 6 x 200                                                                             | 0,40 |
| XSTT3040 | 30-40 | 950  | 700               | 4.700 daN                                                                         | 6                                                                                 | 1,50 mm                                                                           |                                                                                    | 19                                                                                  | 8 x 200                                                                             | 0,55 |
| XSTT4050 | 40-50 | 1050 | 800               | 4.700 daN                                                                         | 6                                                                                 | 1,50 mm                                                                           |                                                                                    | 19                                                                                  | 8 x 200                                                                             | 0,60 |
| XSTT5060 | 50-60 | 1100 | 850               | 4.700 daN                                                                         | 6                                                                                 | 1,50 mm                                                                           |                                                                                    | 19                                                                                  | 8 x 200                                                                             | 0,63 |
| XSTT6080 | 60-80 | 1200 | 900               | 6.000 daN                                                                         | 8                                                                                 | 1,50 mm                                                                           |                                                                                    | 19                                                                                  | 8 x 250                                                                             | 0,85 |

