

STANDARD



[EN] Cable pulling grip with single eye without thimble [D] Kabelziehstrumpf mit Schlaufe [E] Malla tiracables con un lazo sin dedal
[F] Chaussette tire-câbles à boucle simple sans cosse coeur [I] Calza tiracavi con un'asola senza redancia

art.	ø mm	L mm	L ₁ mm				n.		[mm]	kg
JST112/15A	10-15	1400	1250	3.000 daN	5	1,50 mm		7	6 x 100	0,30
JST112/20A	15-20	1400	1250	3.000 daN	5	1,50 mm		7	6 x 100	0,32
JST112/30A	20-30	1400	1250	3.000 daN	5	1,50 mm		7	6 x 100	0,36
JST112/40A	30-40	1450	1250	3.500 daN	6	1,50 mm		7	6 x 150	0,40
JST112/50A	40-50	1450	1250	3.500 daN	6	1,50 mm		7	6 x 150	0,43
JST112/60A	50-60	1450	1250	3.500 daN	6	1,50 mm		7	6 x 150	0,47
JST112/70A	60-70	1450	1250	4.100 daN	7	1,50 mm		7	8 x 150	0,50
JST112/080A	60-80	1450	1250	4.700 daN	8	1,50 mm		7	8 x 150	0,52
JST112/80A	70-80	1450	1250	4.700 daN	8	1,50 mm		7	8 x 150	0,53
JST112/90A	80-90	1450	1250	4.700 daN	8	1,50 mm		7	8 x 150	0,56
JST112/100A	80-100	1450	1250	9.400 daN	8	2,00 mm		7	10 x 150	0,59
JT112/100A	90-100	1500	1250	9.400 daN	8	2,00 mm		7	10 x 200	0,90
JST112/110A	90-110	1500	1250	9.400 daN	8	2,00 mm		7	10 x 200	0,90
JT112/110A	100-110	1500	1250	11.000 daN	10	2,00 mm		7	10 x 200	0,91
JST112/120A	100-120	1500	1250	11.000 daN	10	2,00 mm		7	10 x 200	1,00
JT112/120A	110-120	1500	1250	11.000 daN	10	2,00 mm		7	10 x 200	1,05
JST112/130A	120-130	1500	1250	11.000 daN	10	2,00 mm		7	10 x 200	1,09
JST112/150A	120-150	1500	1250	11.000 daN	10	2,00 mm		7	10 x 200	1,14
JST112/140A	130-140	1550	1250	14.000 daN	12	2,00 mm		7	12 x 200	1,18
JT112/150A	140-150	1550	1250	14.000 daN	12	2,00 mm		7	12 x 200	1,22

