



**[EN]** Cable suspension grip with single eye and thimble made of stainless steel AISI-316, with copper sleeve **[D]** Kabelmontagestrumpf mit einer Kausche aus Edelstahl AISI-316, mit Kupferklemme **[E]** Malla tiracables portadores realizado con un lazo y dedal, fabricado en acero inoxidable AISI-316, con manga de cobre **[F]** Chaussette tire-câbles porteurs, avec simple boucle et cosse cœur, construction en acier inoxydable AISI-316, manchon en cuivre **[I]** Calza di sospensione con un'asola e redancia, realizzate in acciaio INOX AISI-316, manicotto in rame

| art.        | ø mm  | L mm | L <sub>1</sub> mm |           |   |         | n. |   |         | kg   |
|-------------|-------|------|-------------------|-----------|---|---------|----|---|---------|------|
| JZ-KM6100IX | 10-15 | 800  | 600               | 1.100 daN | 5 | 1,50 mm |    | 7 | 9 x 14  | 0,16 |
| JZ-KM6150IX | 16-20 | 800  | 600               | 1.100 daN | 5 | 1,50 mm |    | 7 | 9 x 14  | 0,18 |
| JZ-KM6200IX | 21-27 | 800  | 600               | 1.500 daN | 7 | 1,50 mm |    | 7 | 12 x 18 | 0,21 |
| JZ-KM6300IX | 28-35 | 800  | 600               | 1.500 daN | 7 | 1,50 mm |    | 7 | 12 x 18 | 0,23 |
| JZ-KM6400IX | 36-45 | 800  | 600               | 1.800 daN | 8 | 1,50 mm |    | 7 | 16 x 23 | 0,25 |
| JZ-KM6500IX | 46-55 | 800  | 600               | 3.800 daN | 8 | 2,00 mm |    | 7 | 19 x 27 | 0,44 |
| JZ-KM6600IX | 56-65 | 800  | 600               | 3.800 daN | 8 | 2,00 mm |    | 7 | 19 x 27 | 0,49 |

