



NYLON, REINFORCED



[EN] Reinforced cable suspension grip with single eye without thimble, construction by non-conductive nylon wires **[D]** Kabelmontagestrumpf aus Nylon mit nicht leitender Eigenschaft, mit einer Schlaufe, verstärkte Ausführung **[E]** Malla tiracables portadores con un lazo sin dedal, construcción en hilos de nylon no conductor, versión reforzada **[F]** Chaussette tire-câbles porteurs à boucle simple sans cosse coeur, construction en nylon non-conducteur, version renforcée **[I]** Calza di sospensione con un'asola, costruzione in fili di nylon non conduttore, esecuzione rinforzata

art.	ø mm	L mm	L ₁ mm				n.	 [mm]	kg
JMKM1520NN	15-20	800	600	1.200 daN	5	2,00 mm		8 x 150	0,22
JMKM2030NN	20-30	800	600	1.800 daN	5	2,00 mm		9 x 150	0,25
JMKM3040NN	30-40	850	600	2.200 daN	6	2,00 mm		10 x 150	0,27
JMKM4050NN	40-50	850	600	2.200 daN	6	2,00 mm		10 x 150	0,27
JMKM5060NN	50-60	850	600	2.200 daN	6	2,00 mm		10 x 150	0,27
JMKM6070NN	60-70	900	600	2.500 daN	7	2,00 mm		11 x 150	0,35
JMKM7080NN	70-80	900	600	3.000 daN	8	2,00 mm		12 x 150	0,37
JMKM80100NN	80-100	900	600	3.000 daN	8	2,00 mm		12 x 150	0,40

