




[EN] Cable pulling grip with single eye, laterally open including two closing wires, construction by non-conductive nylon wires

[D] Kabelziehstrumpf mit einer Schlaufe, seitlich offen mit zwei Bindelitzen, gefertigt aus Nylon mit nicht leitender Eigenschaft

[E] Malla tiracables con un lazo, con un lado abierto y dos hilos de coser, construcción en hilos de nylon no conductor

[F] Chaussette tire-câbles a lacet, avec simple boucle, construction en fils de nylon non-conducteur, ouvert latéralement

[I] Calza tiracavi con un'asola, lateralmente aperta con due fili di legatura costruzione in fili di nylon non conduttore

art.	ø mm	L mm	L ₁ mm				n.		kg
JM1520NNAP	15-20	850	700	1.200 daN	5	2,0 mm		5 x 150	0,30
JM2030NNAP	20-30	850	700	1.800 daN	5	2,0 mm		5 x 150	0,33
JM3040NNAP	30-40	950	800	2.200 daN	6	2,0 mm		7 x 150	0,35
JM4050NNAP	40-50	950	800	2.200 daN	6	2,0 mm		7 x 150	0,35
JM5060NNAP	50-60	950	800	2.200 daN	6	2,0 mm		7 x 150	0,35
JM6070NNAP	60-70	1000	850	2.500 daN	7	2,0 mm		8 x 200	0,43
JM7080NNAP	70-80	1000	850	3.000 daN	8	2,0 mm		10 x 200	0,45
JM80100NNAP	80-100	1050	900	3.000 daN	8	2,0 mm		10 x 200	0,48

